



A Furukawa Company

Your Optical Fiber Solutions Partner®

OFS | www.ofsoptics.com

Item # P26764-02, LC Crimp & Cleave Connector

LC Duplex (2 Black Boots) for GiHCS 50/200/230, 62.5/200/230 GiHCS®and 200/230 HCS



[Specifications](#) | [Connector Performance Data](#) | [Cable Design](#) | [Compatibility](#) | [Ordering Information](#)

Specifications	
Color	Black
Connector Type	Duplex
For Use With Optical Fiber Cable Types	<u>Graded-Index 50/200/230 and 62.5/200/230 GiHCS® V-System® cables.</u>

Connector Performance Data	
Typical Insertion Loss @ 850 nm	50/200/230 GiHCS® - 1.0 dB 62.5/200/230 GiHCS® - 1.0 dB
Maximum Insertion Loss @ 850 nm	50/200/230 GiHCS® - 1.5 dB 62.5/200/230 GiHCS® - 1.5 dB
Typical Insertion Loss @ 1300 nm	50/200/230 GiHCS® - 1.2 dB 62.5/200/230 GiHCS® -1.2 dB
Maximum Insertion Loss @ 1300 nm	50/200/230 GiHCS® - 1.7 dB 62.5/200/230 GiHCS® - 1.7 dB

Operating Temperature	-40/+85 °C
Cable Crimp Retention	4.99 lb 22.2 N
Overall Length (without boot)	1.53 Inch 39 mm
Overall Length (with boot installed)	2.18 Inch 55 mm

Cable Design	—
Jacket Diameter	2.2 mm

Compatibility	—
Compatible Termination Kit	DT03732-LC1
Compatible Insertion Loss Test Kit	P10188-15

Ordering Information	—
Order From Location	AVON LOCATION 1.888.438.9936 toll-free in the United States and Canada 1.860.678.0371 from outside the U.S.A. 55 Darling Drive Avon, CT 06001, USA