



A Furukawa Company

Your Optical Fiber Solutions Partner®

OFS | www.ofsoptics.com

Item # BC04265-10, Simplex 2.2 mm Based Construction Step-Index 200 μm HCS® Riser V-System® Cables

OFS 2.2 mm HCS fiber V-System cable is a low-cost, silica-based cabling system, compatible with Avago versatile link 650 nm receivers and transmitters.

Cables built with 200 μm HCS fiber are an alternative to the plastic fiber otherwise used with those components, offering high performance, greater link length, and better mechanical and environmental properties at comparable cost.



[Optical Properties](#) | [Cable Design](#) | [Installation and Usage Specifications](#) | [Ordering Information](#) | [Typical Applications](#) | [Crimp & Cleave Compatibility](#) | [Options](#)

Optical Properties

Type	Multimode Step-Index
Attenuation	@ 850 nm, ≤ 6 dB/km
Fiber Specifications	CF01493-10 , 200 0.37 NA Low OH Optical Fiber

Cable Design

Construction	Simplex
Numerical Aperture	0.37
Fiber Core Diameter	200 ± 4 µm
Outer Cable Diameter	2.2 mm
Cable Weight	5.5 kg/km
Outer Jacket Material	PVC
Outer Jacket Color	Blue
Flammability Rating	UL-1666

Installation and Usage Specifications

Installation Load Maximum	25 lb 111 N
Operating Load Maximum	5 lb 22 N
Minimum Bend Installation	15 mm
Minimum Bend Operating	10 mm
Operating Temperature	-20 to +80 °C
Storage Temperature	-40 to 80 °C

Ordering Information

Product Description Code	HCP-M0200T-V01RK
Order From Location	AVON LOCATION 1.888.438.9936 toll-free in the United States and Canada 1.860.678.0371 from outside the U.S.A. 55 Darling Drive Avon, CT 06001, USA
Order By Item #	BC04265-10

The operating temperature ranges are general guidelines. Consult

Note

with our Technical Sales department to determine the optimal coating and jacketing material for your specific application.
1.860.678.6636

Typical Applications

650 or 850 nm Devices
Factory Automation Near-IR Spectroscopy
Industrial Communications
Laser Power Delivery
Riser Installations

Crimp & Cleave Compatibility

V-Pin Connectors

Options

Also Available in Breakout Construction with up to 18 Sub-Units
Jacket Color
Print Legend
Terminated Assemblies