



4-Fiber 2.2 mm Step-Index 200 μ m HCS® Riser V-System® Fiber Optic Cable

P/N: BC04791-12

Overview

Lightera 2.2 mm HCS fiber V-System cable is a low-cost, silica-based cabling system, compatible with Avago versatile link 650 nm receivers and transmitters. Cables built with 200 μ m HCS fiber are an alternative to the plastic fiber otherwise used with those components, offering high performance, greater link length, and better mechanical and environmental properties at comparable cost.

Typical Applications

- 650 or 850 nm Devices
- Factory Automation
- Industrial Communications
- Laser Power Delivery
- Near-IR Spectroscopy
- Riser Installations

Product Specifications	
Product Description	4-Fiber 2.2 mm Step-Index 200 μm HCS Riser V-System Fiber Optic Cables
Physical Characteristics	
Construction	4-Fiber
Numerical Aperture	0.37
Fiber Core Diameter	200 $\pm$ 4 μ m
Sub-Unit Diameter	2.2 $\pm$ 0.1 mm
Outer Cable Diameter	7.5 mm
Cable Weight	50 kg/km
Outer Jacket Material	PVC
Outer Jacket Color	Black
Flammability Rating	UL-1666
Crimp & Cleave Compatibility	V-Pin Connectors
Optical Characteristics	
Type	Multimode Step-Index
Attenuation @ 850 nm	$\leq$ 8 dB/km
Fiber Specifications	CF01493-10, 200 μ m HCS 0.37 NA Low OH Optical Fiber
Mechanical and Environmental	
Installation Load (Maximum)	90 lb. (400 N)
Operating Load (Maximum)	45 lb. (200 N)
Minimum Bend Installation	113 mm
Minimum Bend Operating	75 mm
Operating Temperature	-20 to +80 $^{\circ}$ C
Storage Temperature	-40 to +80 $^{\circ}$ C
Order by Part Number	BC04791-12
Product Description Code	HCP-M0200T-V04RB
OPTIONS	Jacket color, print legend, terminated assemblies
NOTE	The operating temperature ranges are general guidelines. Consult with our Technical Sales department to determine the optimal coating and jacketing material for your specific application. 1.860.678.6636.
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.