



GiHCS® 50/200/230 μ m Zipcord Fiber Optic Cable

P/N: C26136

Overview	The GiHCS optical cable family takes advantage of the high strength characteristics of HCS® fluoroacrylate coating technology while improving bandwidth through Graded-Index optical fiber design. Most similar to OM-2 level fiber optic cables, GiHCS cables support Fast and Gigabit Ethernet, provide LSZH and OFNR Riser fire-safety ratings, and include both indoor and indoor/outdoor cable designs. These industrialized cables are crimp & cleave compatible for quick, easy field connectorization in harsh environments.
Typical Applications	• Nuclear Power Plants • Offshore Marine Platforms • Shipboard Systems • Wind Turbines

Product Specifications	
Product Description	2.2 mm Zipcord 50/200/230 Low Smoke Zero Halogen
Physical Characteristics	
Fiber Core Diameter	50 μ m
Fiber Geometry	50/200/230 μ m
Construction	Zipcord
Specialty Testing (Cyclic Flexing)	> 50,000 Cycles
Outer Cable Diameter	2.2 $\pm$ 0.1 mm x 4.6 Nominal
Cable Weight	< 12.0 kg/km
Outer Jacket Material	LSZH
Outer Jacket Color	Orange
Crimp & Cleave Compatibility	V-Pin Connectors
Optical Characteristics	
Type	Multimode Graded-Index
Attenuation @ 1300 nm	$\leq$ 3.0 dB/km
Attenuation @ 850 nm	$\leq$ 5.0 dB/km
Fiber Specifications	F16496, 50 μ m GiHCS® Optical Fibers
Mechanical and Environmental	
Installation Load (Maximum)	25 lb. (111 N)
Operating Load (Maximum)	5 lb. (22 N)
Minimum Bend Installation	33 mm
Minimum Bend Operating	22 mm
Operating Temperature	-20 to +80 °C
Storage Temperature	-40 to +80 °C
Intended Location	Indoor
Order by Part Number	C26136
Product Description Code	HCN-MF050T-V02ZZ
OPTIONS	Also available in breakout construction with up to 18 sub-units, jacket color, outer jacket material, print legend, terminated assemblies
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.